

THERMOAQUA

Hot Showers and More !

ATMOR Singlepoint Instantaneous Water Heater designed to supply continuous hot water on demand. Ideal for open vented point-of-use application.



Safety Features:

- Fully automatic operation
- Auto Shut-off (at 55°C)
- Equipped with Pressure Relief Valve (PRV)
- User Friendly buttons and switches
- Heating Chamber made of High Grade Composite Materials

Atmor Singlepoint For Shower only

TECHNICAL SPECIFICATIONS

TECHNOLOGY/STANDARD	GERMAN STANDARD TECHNOLOGY		
TYPE	Electric Instantaneous (demand) Water Heater		
OPERATION	Fully Automatic		
ACTIVATING MECHANISM	Diaphragm Type		
TEMPERATURE SELECTION	Three-way temperature selection		
SAFETY	Auto-thermal cut-off at 52°C to 55°C; final cut-off at 80°C + 10%		
APPLICATION	For open vented point-of-use application (e.g. showers)		
VOLTAGE	220-240 VAC		
POWER RATING	3.5 Kilowatts		
CYCLES	50 Hz - 60 Hz		
PHASE	Single Phase		
POWER/HEAT SETTING	Low: 1.5 Kw	Med: 2.0 Kw	High: 3.5 Kw
KILOWATT LOADING	220 VAC; 3.5 Kw	230 VAC; 3.5 Kw	240 VAC; 3.8 Kw
RECOMMENDED CABLE SIZE	2.5 / 4 sq. mm		
RECOMMENDED CIRCUIT BREAKER RATING	30 Amperes		
CABLE ENTRY	Top right and Top left		
WEIGHT	1.25 Kgs.		
HEIGHT	190 mm		
WIDTH	300 mm		
DEPTH	110 mm		
INLET/OUTLET CONNECTION	15 mm (1/2 compression inlet connection)		
FLOW RATE	4 Liters / Minute (1.05 Gallons / Minute) @ 12 C°Temp.Rise		
MINIMUM ACTIVATING PRESSURE	2.5 PSI (Pounds per Square Inch)		

**Sales Office : Unit 606, No.21 Cristobal Place, Ignacio Santos
Diaz St. cor. Cristobal St., Brqy. Kaunlaran, Cubao, Quezon City
(02) 8638-0967 / 0995-0151925 / 0923-6457536**